

- GRUPPI STATICI
- POWER SOLID STATE RELAYS
- HALBLEITERRELAIS

- GROUPES STATIQUES DE PUISSANCE
- GRUPOS ESTÁTICOS
- GRUPOS ESTÁTICOS



CROSS REF TABLE - OLD CODES > NEW CODES
code **80275** edition **12-2014**

OLD CODE	NEW CODE	DESCRIPTION
15 Ampere		
GTS-15/230-0	GTS-15/24-D-0	15A-230Vac (15A a 40°C; voltage range 24...280Vac)
GTS-15/480-0	GTS-15/48-D-0	15A-480Vac (15A a 40°C; voltage range 24...530Vac)
	GTS-15/60-D-0	15A-600Vac (15A a 40°C; voltage range 24...660Vac)
25 Ampere		
GTS-25/230-0	GTS-25/24-D-0	25A-230Vac (25A a 40°C; voltage range 24...280Vac)
GTS-25/480-0	GTS-25/48-D-0	25A-480Vac (25A a 40°C; voltage range 24...530Vac)
	GTS-25/60-D-0	25A-600Vac (25A a 40°C; voltage range 24...660Vac)
40 Ampere		
GTS-40/230-0	GTS-40/24-D-0	40A-230Vac (40A a 40°C; voltage range 24...280Vac)
GTS-40/480-0	GTS-40/48-D-0	40A-480Vac (40A a 40°C; voltage range 24...530Vac)
	GTS-40/60-D-0	40A-600Vac (40A a 40°C; voltage range 24...660Vac)
50 Ampere		
GTS-50/230-0	GTS-50/24-D-0	50A-230Vac (50A a 40°C; voltage range 24...280Vac)
GTS-50/480-0	GTS-50/48-D-0	50A-480Vac (50A a 40°C; voltage range 24...530Vac)
	GTS-50/60-D-0	50A-600Vac (50A a 40°C; voltage range 24...660Vac)
	GTS-50/60-D-2	50A-600Vac (50A a 40°C; voltage range 24...660Vac); total load failure alarm with isolated contact (NC)

OLD CODE	NEW CODE	DESCRIPTION
60 Ampere		
GTS-60/230-0	GTS-60/24-D-0	60A-230Vac (60A a 40°C; voltage range 24...280Vac)
GTS-60/480-0	GTS-60/48-D-0	60A-480Vac (60A a 40°C; voltage range 24...530Vac)
	GTS-60/60-D-0	60A-600Vac (60A a 40°C; voltage range 24...660Vac)
	GTS-60/60-D-2	60A-600Vac (60A a 40°C; voltage range 24...660Vac); total load failure alarm with isolated contact (NC)

75 Ampere

GTS-75/230-0	GTS-75/24-D-0	75A-230Vac (75A a 40°C; voltage range 24...280Vac)
GTS-75/480-0	GTS-75/48-D-0	75A-480Vac (75A a 40°C; voltage range 24...530Vac)
	GTS-75/60-D-0	75A-600Vac (75A a 40°C; voltage range 24...660Vac)
	GTS-75/60-D-2	75A-600Vac (75A a 40°C; voltage range 24...660Vac); total load failure alarm with isolated contact (NC)

90 Ampere

GTS-90/230-0	GTS-90/24-D-0	90A-230Vac (90A a 40°C; voltage range 24...280Vac)
GTS-90/480-0	GTS-90/48-D-0	90A-480Vac (90A a 40°C; voltage range 24...530Vac)
	GTS-90/60-D-0	90A-600Vac (90A a 40°C; voltage range 24...660Vac)
	GTS-90/60-D-2	90A-600Vac (90A a 40°C; voltage range 24...660Vac); total load failure alarm with isolated contact (NC)

120 Ampere

GTS-120/230-0 VEN91	GTS-120/24-D-0 VEN91	120A-230Vac (120A a 40°C; voltage range 24...280Vac); fan p.s. 115Vac
GTS-120/230-0 VEN90	GTS-120/24-D-0 VEN90	120A-230Vac (120A a 40°C; voltage range 24...280Vac); fan p.s. 230Vac
GTS-120/480-0 VEN91	GTS-120/48-D-0 VEN91	120A-480Vac (120A a 40°C; voltage range 24...530Vac); fan p.s. 115Vac
GTS-120/480-0 VEN90	GTS-120/48-D-0 VEN90	120A-480Vac (120A a 40°C; voltage range 24...530Vac); fan p. s. 230Vac
	GTS-120/60-D-0 VEN91	120A-600Vac (120A a 40°C; voltage range 24...660Vac); fan p.s. 115Vac
	GTS-120/60-D-2 VEN91	120A-600Vac (120A a 40°C; voltage range 24...660Vac); fan p.s. 115Vac; total load failure alarm with isolated contact (NC)
	GTS-120/60-D-0 VEN90	120A-600Vac (120A a 40°C; voltage range 24...660Vac); fan p.s. 230Vac
	GTS-120/60-D-2 VEN90	120A-600Vac (120A a 40°C; voltage range 24...660Vac); fan p.s. 230Vac; total load failure alarm with isolated contact (NC)