



M80

The rigid stem configuration makes installation fast and easy.



M81

The flexible configuration is designed for applications requiring further thermal isolation or where installation would be otherwise difficult or impractical.

Main features

The M8 Series is a melt pressure monitoring system which comes complete with the following items:

- M3x-6-M-xxxx-1-4-D-000 (melt pressure transducer)
- 40TB-10-RRR-1-0-1 (1/4 DIN pressure indicator)
- C08WLS (25 foot 6-pin cable)
- SF18 (mounting bracket)

Indicator:

- Economically priced
- Displays pressure in a 4-digit LED display
- Auto zero
- Auto span
- Auto calibration
- 2 alarms with adjustable setpoint
- Touch-type keypad
- Built-in strain gauge bridge excitation
- Filter for digit stabilization
- Coded access for user lockout

Transducer:

- Better than $\pm 0.50\%$ accuracy
- Fluid-filled system for temperature stability
- 80% output signal for easy calibration
- 15-5 PH stainless steel diaphragm with GTP coating

The M8 Series is an excellent solution for those who wish to have the accuracy and stability of a transducer and digital indicator at a great price.

TECHNICAL SPECIFICATIONS

See data sheets for M3 and 40TB-10-RRR-1-0-1 for more information.

ACCESSORIES

Connectors

6-pin mating connector (IP65 protection degree)CON300

Extension cables

6-pin connector with 8m (25ft) cableC08WLS (standard)

6-pin connector with 15m (50ft) cableC15WLS *

6-pin connector with 25m (75ft) cableC25WLS *

6-pin connector with 30m (100ft) cableC30WLS *

* Consult factory for ordering and pricing

Accessories

Mounting bracketSF18


Dummy plug for 1/2-20UNFSC12

Drill kit for 1/2-20UNFKF12

Cleaning kit for 1/2-20UNFCT12

Cable Wiring Code

Function	Wire
Sig (+)	Red
Sig (-)	Black
Exc (+)	White
Exc (-)	Green
Cal	Blue
Cal	Brown



Examples

M81-6-M-B07C-1-4-D-000

Melt pressure monitoring system (1/4 DIN) with rigid stem and flex transducer, 6-pin connector/cable, 1/2-20 UNF thread, 700 bar full scale output, 0.50% accuracy class, 153 mm (6") rigid stem, 457 mm (18") flex

M80-6-M-P03M-1-4-0-000

Melt pressure monitoring system (1/4 DIN) with rigid stem transducer, 6-pin connector/cable, 1/2-20 UNF thread, 3000 psi full scale output, 0.50% accuracy class, 153 mm (6") rigid stem

GEFRAN reserves the right to make any kind of design or functional modification at any moment without prior notice.