

G-VISION ADVANCED PANEL PC



Display from 7" to 21"



INDUSTRY 4.0



MULTI TOUCH



TOP PERFORMANCES



WEB SERVER



CONNECTIVITY



CLOUD

GEFRAN

BEYOND TECHNOLOGY



* Controller communication only. Not master

INTEGRATED WIFI
only model 67

FIELDBUS COMMUNICATION

EVENT MANAGEMENT

SCALABLE

HTML

INTEGRATED PLC

INTEGRATED CYBER SECURITY FIREWALL

TECHNICAL DATA

SYSTEM RESOURCES				
MODEL	G-Vision 66-070-54-00-00	G-Vision 66-101-54-00-00	G-Vision 66-156-54-00-00	G-Vision 66-215-54-00-00
Display - Colors	TFT 7" - 16:9 LED - 16M	TFT 10,1" - 16:9 LED - 16M	TFT 15,6" - LED 16M	TFT 21,5" - LED 16M
Resolution	800x480 WVGA	1280x800 WXGA	1366x768, HD	1920x1080, full HD
MODEL	G-Vision 67-070-54-00-00	G-Vision 67-101-54-00-00	G-Vision 67-156-54-00-00	G-Vision 67-215-54-00-00
Display - Colors	TFT 7" - 16 M	TFT 10,1" - 16M	TFT 15,6" - 16 M	TFT 21,5" - 16M
Resolution	1024x600	1280x800	1366*768	1920x1080
Touchscreen	True Glass Projected Capacitive, Multitouch			
CPU	64-bit RISC quad core - 1.6 GHz			
Operating System	Linux			
Flash	4 GB			
RAM	2 GB			
INTERFACE				
MODEL	G-Vision 66		G-Vision 67	
Porta Ethernet	3 (port 0 - 10/100/1000, port 1 - 10/100, port 2 - 10/100)		10/100 PoE	
Porta USB	2 (Host V2.0, max. 500 mA)		1 (Host V2.0, max. 500 mA, available with special cable)	
Serial port	1 (RS-232, RS-485, RS-422, software configurable). Max 3 serial ports using plug-in modules.		-	
SD card	Si		-	
NFC	-		ISO/IEC 14443A	
Wi-Fi	-		IEEE 802.11a/b/g	