



The rigid stem configuration makes installation fast and easy.



The flexible configuration is designed for applications requiring further thermal isolation or where installation would be otherwise difficult or impractical.

Main features

The W0 Series is a melt pressure control system which comes complete with the following items:

- W3x-6-M-xxxx-1-4-D-000 (oil-filled melt pressure transducer)
- 2500-0-0-0-W-0-1 (pressure controller)
- C08WLS (25 foot 6-pin cable)
- SF18 (mounting bracket)

Controller:

- Economically priced
- Displays pressure in a 5-digit LED display
- Auto zero
- Auto span
- Auto calibration
- 4 alarms with adjustable setpoint
- Touch-type keypad
- Built-in strain gauge bridge excitation
- Filter for digit stabilization
- Coded access for user lockout

Transducer:

- Better than $\pm 0.50\%$ accuracy
- Fluid-filled system for temperature stability
- 80% output signal for easy calibration
- 17-7 PH stainless steel corrugated diaphragm with GTP coating
- Oil-fill is FDA approved — meets requirements CFR172.3620 and CFR172.878

The W0 Series is an excellent solution for those who wish to have the accuracy and stability of a transducer and digital controller at a great price.

TECHNICAL SPECIFICATIONS

See data sheets for W3 and 2500-0-0-0-W-0-1 for more information.

ACCESSORIES

Connectors

6-pin mating connector (IP65 protection degree)CON300

Extension cables

6-pin connector with 8m (25ft) cableC08WLS (standard)

6-pin connector with 15m (50ft) cableC15WLS *

6-pin connector with 25m (75ft) cableC25WLS *

6-pin connector with 30m (100ft) cableC30WLS *

* Consult factory for ordering and pricing

Accessories

Mounting bracketSF18


Dummy plug for 1/2-20UNFSC12

Drill kit for 1/2-20UNFKF12

Cleaning kit for 1/2-20UNFCT12

Cable Wiring Code

Function	Wire
Sig (+)	Red
Sig (-)	Black
Exc (+)	White
Exc (-)	Green
Cal (+)	Blue
Cal (-)	Brown



Examples

W01-6-M-B07C-1-4-D-000

Melt pressure control system with rigid stem and flex transducer, 6-pin connector/cable, 1/2-20 UNF thread, 700 bar full scale output, 0.50% accuracy class, 153 mm (6") rigid stem, 457 mm (18") flex

W00-6-M-P03M-1-4-0-000

Melt pressure control system with rigid stem transducer, 6-pin connector/cable, 1/2-20 UNF thread, 3000 psi full scale output, 0.50% accuracy class, 153 mm (6") rigid stem

GEFRAN reserves the right to make any kind of design or functional modification at any moment without prior notice.